



SYGD10146

Product Data

Diameter	0.003in, 0.004in, 0.005in, 0.006in, 0.008in, 0.012in, 0.016in, 0.018in, 0.01in, 0.02in
Break Strength	10lb, 15lb, 20lb, 25lb, 30lb, 40lb, 50lb, 60lb, 80lb, 9lb
Material	Polyethylene
Length	124yds 328 yds 547yds 129yds
Strands	4

Product Pictures

Product pictures showing various views of the twine. On the left, there are several rolls of twine. On the right, there are four numbered diagrams illustrating different applications: 01 shows a knot, 02 shows a twine being used to tie a net, 03 shows twine being used to secure a net to a post, and 04 shows twine being used to secure a net to a boat.

Product Data

Diameter	0.003in, 0.004in, 0.005in, 0.006in, 0.008in, 0.012in, 0.016in, 0.018in, 0.01in, 0.02in
Break Strength	10lb, 15lb, 20lb, 25lb, 30lb, 40lb, 50lb, 65lb, 80lb, 8lb
Material	Polyethylene
Length	124yds 328 yds 547yds 1094yds
Strands	4
Custom MOQ	500pcs
Custom Price	Depends on different options, 3%-10% higher than basic price
Lead Time	30-45 days

Product Pictures





01 COLORFAST AND KNOT WELL



02 PRACTICALLY ZERO EXTENSIBILITY AND ULTRA-SENSITIVITY



03 4 STRANDS PE LINE, SUPERIOR ABRASION RESISTANCE



04 FASTER CUTTING WATER



PRODUCT INFORMATION

ABOUT TENSILE PARAMETERS



LINE NUMBER	DIAMETER(IN)	BREAKING STRENGTH(LB)
0.15	0.003	8
0.4	0.004	10
0.6	0.005	15
1	0.006	20
1.5	0.008	25
2.5	0.01	30
3.5	0.012	40
6	0.016	50
7	0.018	65
8	0.02	80

